


# Fire Sprinkler Stationary Compressors

## Base Plate Mounted

### Standard Features

- Heavy-duty single stage cast iron compressor pump  
Made in Somerset, PA USA
- Splash lubricated
- Belt driven with a large flywheel for extra cooling and easier start-up
- Each unit is filled with Jenny Synthetic Blue Compressor Pump Oil

- Directional air shroud for reduced pump temperatures
- Totally enclosed heavy-duty belt guard
- Powder coated, extra heavy steel base plate
- Large canister intake filter with replaceable filter elements
- Magnetic starter is included on all 5HP and larger units
- Industrial/Commercial grade UL Listed electric motor
- Thermal overload motor protection



### Base Mounted

#### System Size

Maximum Gallons in system to be pumped to 40 PSI in 30 Minutes

Model	Pump	HP	Power Supply	Pump RPM	CFM del'd @ 40 PSI	Optional Auto Control Group
220	F13S-BS	1/3	115 Volt (through 2 HP) or 230 Volt 1 Phase	670	2.9	ACGF
290	F12S-BS	F 1/2		950	3.8	
350	F34S-BS	K 3/4		1200	4.4	
425	K34S-BS	K	1	520	5.3	ACGK
480	F1S-BS	F		1430	6.0	ACGF
600	K1S-BS	K	1-1/2	790	7.4	ACGK
885	K15S-BS	K		1140	10.9	
985	K2S-BS		2	1280	12.4	ACGD
1215	G2S-BS		3	630	15.1	
1775	G3S-BS	G		950	21.8	
1950	GC5S-BS		5	1030	24.2	ACGJ
2115	J5S-BS	J		830	26.0	

### Tank Mounted/30 Gallon

Model	Pump	HP	Power Supply	Pump RPM	CFM del'd @ 40 PSI
220	F13S-30UMS	1/3	115 Volt (through 2 HP) 230 Volt 1 Phase	670	2.9
290	F12S-30UMS	F 1/2		950	3.8
350	F34S-30UMS	K 3/4		1200	4.4
425	K34S-30UMS	K	1	520	5.3
480	F1S-30UMS	F		1430	6.0
600	K1S-30UMS	K	1-1/2	790	7.4
885	K15S-30UMS	K		1140	10.9
985	K2S-30UMS		2	1280	12.4
1215	G2S-30UMS		3	630	15.1
1775	G3S-30UMS	G		950	21.8
1950	GC5S-30UMS	GC	5	1030	24.2
2115	J5S-30UMS	J		830	26.0

## Tank Mounted

### Additional Standard Features

- Tanks are powder coated and ASME certified
- Protectively mounted fittings
- Manual tank drain(s)
- Large canister intake filter with replaceable filter elements
- Special unloading valves to assist in motor starting
- Tank gauge
- Pressure relief safety valve
- Auto Start/Stop control with pressure unloader set at 25-40 PSI

### Options

- ASME National Board tank
- Magnetic starter
- 17 gallon tank
- Vertical tank
- Low oil level switch
- Oil sight glass
- Automatic tank drain
- Air line filter
- Aftercooler
- Dryer
- Control Group



F12S-30S



GC5S-30S



K15S-30S